

Communication Test Report

Name of test engineer(s): Jesse Saastamoinen
 Date: 2014-12-09
 Tested device/module/component: V265
 Firmware version: V.10.159
 Vampset version: V2.2.158
 Simple tester version: V1.0.4.110
 IEC 61850 Simple tester version: 04.06.2012

TEST ARRANGEMENT:

PC to V6CP10 using the front serial port (VAMPSET v.2.2.154).

PC to V6CP10 serial interface using the RS-232 serial cable.

PC to V6CP10 ethernet interface using the standard Ethernet network.

V6CP10	PC (USB to RS-232 converter)
Pin 2	Pin 2
Pin 3	Pin 3
Pin 7	Pin 5




Figure 1. Test arrangement

RESULTS:

Test no.	Test description	Expected result	Pass / Fail	Remarks
1	-Select SpaBus protocol and set VI1=0 in the relay -Start Simple Tester -Write SpaBus data 69I1=1 -Events when data is written ? -Read SpaBus data 69I1	-Simple Tester status shows OK -VI1 = 1 -Event 69E1 -Value = 1	Not tested	
2	-Select ModBusSlv protocol and set VI1=0 in the relay -Start Simple Tester -Write modbus reg 3427=1 -Events when data is written ? -Read Modbus reg 3427	-Simple Tester status shows OK -VI1 = 1 -Event 4417 -Value = 1	Not tested	
3	-Select IEC 103 protocol and set VI1=0 in the relay -Set IEC 103 conf. as Note 3. -Start Simple Tester -Write FUN 55 INF 161=1 -Events when data is written ? -Read	-Simple Tester status shows OK -VI1 = 1 -Event FUN 55 INF 161 -Value = 2 (this is equal to ON)	Not tested	
4	-Select DNP3 protocol and set VI1=0 in the relay -Set IEC DNP conf. as Note 4. -Start Simple Tester -Write BO index 0 (direct) = 1 -Events when data is written ? -Read BI index 0	-Simple Tester status shows OK -VI1 = 1 -Event "BI 0 CHANGE Value 1:" -Value = 1	Not tested	
5	-Select IEC 101 protocol and set VI1=0 in the relay -Set IEC 101 conf. as Note 5. -Start Simple Tester -Write Point index 32769 (single, direct) = 1 -Events when data is written ? -Read Point index 2	-Simple Tester status shows OK -VI1 = 1 -Event "IOA 00002....SPI 1" -Value = 1	Not tested	

Test no.	Test description	Expected result	Pass / Fail	Remarks
6	<ul style="list-style-type: none"> -Select ModBusTCP protocol for the Ethernet port and set VI1=0 in the relay -Start Simple Tester -Write modbus reg 3427=1 -Events when data is written ? -Read Modbus reg 3427 	<ul style="list-style-type: none"> -Simple Tester status shows OK -VI1 = 1 -Event 4417 -Value = 1 	Pass	
7	<ul style="list-style-type: none"> -Select DNP3 protocol for the Ethernet port and set VI1=0 in the relay -Set IEC DNP conf. as Note 4. -Start Simple Tester -Write BO index 0 (direct) = 1 -Events when data is written ? -Read BI index 0 	<ul style="list-style-type: none"> -Simple Tester status shows OK -VI1 = 1 -Event "BI 0 CHANGE Value 1:" -Value = 1 	Pass	
8	<ul style="list-style-type: none"> -Select IEC 61850 protocol for the Ethernet port and set VI1=0 in the relay -Set IEC 61850 conf as Note 8. -Start 61850 Simple Tester -Enable events by "VI1GGIO137/SPCSO/StVal – Enable RCB" see Note 8. -Write VI1GGIO137/SPCSO/Oper=True -Events when data is written ? -Read VI1GGIO137/SPCSO/StVal 	<ul style="list-style-type: none"> -61850 Simple Tester Status "Connected" -VI1 = 1 -Report Value = True -Value = True 	Pass	
9	<ul style="list-style-type: none"> -Select EthernetIP protocol for the Ethernet port and set VI1=0 in the relay -Set EthernetIP conf as Note 9. -Start Simple Tester -Write Class/Instanceld/Attributeld (100/1/107) = 1 -Events when data is written ? -Read Class/Instanceld/Attributeld (100/1/107) 	<ul style="list-style-type: none"> -Simple Tester status shows OK -VI1 = 1 -Event 69E01 -Value = 1 	Pass	
10	<ul style="list-style-type: none"> -Select IEC 101 protocol and set VI1=0 in the relay -Set IEC 101 conf. as Note 5. -Start Simple Tester -Write Point index 32769 (single, direct) = 1 -Events when data is written ? -Read Point index 2 	<ul style="list-style-type: none"> -Simple Tester status shows OK -VI1 = 1 -Event "IOA 00002....SPI 1" -Value = 1 	Pass	

Test no.	Test description	Expected result	Pass / Fail	Remarks
11	<ul style="list-style-type: none"> -Select ProfibusDP protocol for the Remote port and set VI1=0 in the relay -Make conf. as in Note 10. -Start HMS ProfibusDP master simulator -Write Output Data byte 2 =1 -Read Input Data byte 1 	<ul style="list-style-type: none"> -Master simulator status = Connected -VI1 = 1 -Value = 00000001 	Not tested	

Note 3: IEC 103 Configuration:


Digital						
Index	FUN	IINF	GI	EVENT	CONTROL	Item
[000]	55	161	X	X	X	Virtual input 1

Note 4: DNP 3 Configuration:


DNP3: DATA POINTS - BO	
Binary 0	
Index	Item
0	VI1

DNP3: DATA POINTS - BI			
Binary Inputs			
Index	Class	UR	Item
0	1	Off	VI1

Note 5: IEC 101 Configuration:



Note 8: IEC 61850 Configuration:



61850 Simple tester, enable events from VI1

Report

LN	VI1GGI0137	Obj	SPCSO	Attr	stVal	Value	Enable RCB
							Disable RCB

61850 Simple tester, control of VI1:

Control

LN	VI1GGI0137	Obj	SPCSO	Attr	Oper	Value	True	Execute
----	------------	-----	-------	------	------	-------	------	---------

Note 9: EthernetIP Configuration:

CIP I/O configuration

Producing Assembly (Tx, T->0)

Name	Length	Scaling	Offset
Control Supervisor#010 / Faulted	1	1 = 1	000
Digital#169 / DevStatus	1	1 = 1	001
Digital#107 / Virtual input 1	1	0,1	002

Consuming Assembly (Rx, 0->T)

Name	Length	Scaling	Offset
Control Supervisor#012 / FaultRst	1	1 = 1	000
Digital#107 / Virtual input 1	1	0,1	001

Writing to Virtual input 1:

Class	100	Instanceid	1	Attributeld	107	Value	0	Size	1	Status	Success	Write
-------	-----	------------	---	-------------	-----	-------	---	------	---	--------	---------	-------

Reading virtual input 1:

Class	100	Instanceid	1	Attributeld	107	Result	0	Read
-------	-----	------------	---	-------------	-----	--------	---	------

Final conclusion:

The following protocols have been found to work with writing/reading of Virtual Input 1 and event generation from change of Virtual input 1.

- ModbusTCP
- DNP3 (TCP)
- IEC 101 (TCP)
- IEC 61850
- EthernetIP

Based on communication tests firmware version 10.159 can be released.