

IEC 61850 Certificate Level A¹

Page 1/2

ssued to:

Schneider Electric – Vamp Oy Yrittäjänkatu 15 P.O. Box 810 65101 Vaasa Finland No. 74105137-MOC/INC 13-4042

For the server product: VAMP300

SW version: 10.135

Serial Number: 000717

Issued by:



The server product has not shown to be non-conforming to:

IEC 61850 First Edition Parts 6, 7-1, 7-2, 7-3, 7-4 and 8-1

Communication networks and systems in substations

The conformance test has been performed according to IEC 61850-10, the UCA International Users Group Device Test Procedures version 2.3 with TPCL² version 1.7, the product's protocol, model and technical issue implementation conformance statements and extra information for testing: "VAMP protection relays with embedded IEC 61850 Server Conformance Statement for VAMP 300, VAMP 321, version 0.2.2".

The following IEC 61850 conformance blocks have been tested with a positive result (number of relevant and executed test cases / total number of test cases):

1 Basic Exchange (20/24)

2 Data Sets (3/6)

2+ Data Set Definition (23/23)

5 Unbuffered Reporting (15/19)

6 Buffered Reporting (17/21)

9a GOOSE Publish (11/13)

9b GOOSE Subscribe (10/11)

12a Direct Control (6/12)

12b SBO Control (8/14)

12c Enhanced Direct Control (6/13)

12d Enhanced SBO Control (11/19)

13 Time Synchronization (3/5)

14 File Transfer (6/7)

This certificate includes a summary of the test results as carried out at InfoTech in Poland with UniCA 61850 Client simulator 4.26.04 with test suite 3.23.00 and UniCA 61850 Analyzer 5.27.07. This document has been issued for information purposes only, and the original paper copy of the KEMA report No. 74105137-MOC/INC 13-4043 will prevail.

The test has been carried out on one single specimen of the product as referred above and submitted to KEMA by Schneider Electric - VAMP Oy. The manufacturer's production process has not been assessed. This attestation does not imply that KEMA has approved any product other than the specimen tested.

Arnhem, November 21, 2013

M. Adriaensen

Director Intelligent Networks & Communication

R Schimmel Certification Manager

¹ Level A - Independent test lab with certified ISO 9001 Quality System

² TPCL - Test procedures change list

Copyright © KEMA Nederland B.V., Arnhem, the Netherlands. All rights reserved. Please note that any electronic version of this KEMA attestation is provided to KEMA's customer for convenience purposes only. It is prohibited to update or change it in any manner whatsoever, including but not limited to dividing it into parts. In case of a conflict between the electronic version and the original version, the original paper version issued by KEMA will prevail.



Applicable Test Procedures from the UCA International Users Group Device Test Procedures version 2.3 with TPCL version 1.7

Conformance Block	Mandatory	Conditional
1: Basic Exchange	Ass1, Ass2, Ass3, AssN2, AssN3, AssN4, AssN5	Srv6, Srv7, Srv8, SrvN1e, SrvN1f, SrvN3
	Srv1, Srv2, Srv3, Srv4, Srv5, SrvN1abcd, SrvN4	
2: Data Sets	Dset1, Dset10a, DsetN1ae	
2+: Data Set Definition	Dset2, Dset3, Dset4, Dset5, Dset6, Dset7, Dset8, Dset9	
	DsetN1cd, DsetN2, DsetN3, DsetN4, DsetN5, DsetN6, DsetN7, DsetN8, DsetN9, DsetN10, DsetN11, DsetN12, DsetN13, DsetN14, DsetN15	
5: Unbuffered Reporting	Rp1, Rp2, Rp3, Rp4, Rp7, Rp10, Rp12, RpN1, RpN2, RpN3, RpN4	Rp6, Rp8, Rp9, RpN5
6: Buffered Reporting	Br1, Br2, Br3, Br4, Br7, Br8, Br9, Br12, Br14, BrN1, BrN2, BrN3, BrN4, BrN5	Br6, Br10, Br11
9a: GOOSE publish	Gop2, Gop3, Gop4, Gop7, Gop9, Gop10a	Gop1, Gop5, Gop6, Gop8, GopN1
9b: GOOSE subscribe	Gos1a, Gos2, Gos3, GosN1, GosN2, GosN3, GosN4, GosN5, GosN6	Gos1b
12a: Direct control	CtIN3, CtIN8, DOns1	Ctl2, CtlN11, DOns3
12b: SBO control	Ctl3, CtlN1, CtlN2, CtlN3, CtlN4, SBOns2	Ctl2, CtlN11
12c: Enhanced Direct Control	CtIN3, CtIN8, DOes2, DOes5	Ctl2, CtlN11
12d: Enhanced SBO control	Ctl3, CtlN1, CtlN2, CtlN3, CtlN4, CtlN9, SBOes1, SBOes2, SBOes3	Ctl2, CtlN11
13: Time sync	Tm1, Tm2, TmN1	
14: File transfer	Ft1, Ft2ab, Ft4, FtN1ab	Ft2c, FtN1c

All configuration file and data model tests have been successfully performed for the product variants using the same communication hardware and software version: VAMP321.